

### MODEL T-646I/T-627WH TAPE APPLICATION SYSTEM

The T-646I/T-627WH Tape Application System semi-automatically applies strips and/or spots of many adhesive transfer and double coated tapes to flat surfaces.

#### FEATURES

- Product conveying speed adjustable up to 150 ft. /min.
- Accommodates product up to 1¼" thick, 2¼" - 55" wide
- Accommodates ¼" to 1" wide tape
- Two applicators standard; accommodates up to six applicators with modifications
- Individual tape head programming.
- Touch screen operator interface.
- Displays characters in English, French, Spanish or Dutch.
- Displays numbers in inches or millimeters.
- Product batch count.
- Machine available in (4) widths 18", 30", 43" and 55".

#### OPTIONS

- T-627H2 Tape Applicator to apply up to 2" wide tapes
- Tape pre-stripper for high unwind tapes
- Product stabilization head
- Liner rewind or liner plow to apply double coated tape liner removed.
- SF-20 Automatic Feeder for the T-646I 2.25" to 18" wide x 5" to 17" long, 28 lb paper minimum.



#### PRODUCT SPECIFICATIONS

(Depending on product and tape)

Tape Strip Length: 1.0" minimum (25mm)

Tape Strip Margin: .13" from leading edge (3mm)

Tape Start & Stop Tolerance: ±.09 (±2.3mm)

Tape Strip Gap: 1" minimum (25mm)

#### MACHINE & POWER SPECIFICATION

Electrical: 115/230V, 1Ph, 50/60Hz

Air: 80 PSI (550 kPa) ¼" NPT

Size: Varies by unit

Speed: Up to 150 ft. /min.

Weight: Varies by size of unit

See Straub for engineered tape solutions in a variety of industries, from automotive and packaging to solar. If we don't have the tape applicator you need, we'll design, build and install a custom solution for you.